



# NTN BEARING MFG.CORP



TB-24TC Bearing 2D drawings and 3D CAD models

1.5 Inch | 38.1 Millimeter x 1.938 Inch | 49.225 Millimeter x 1.938 Inch | 49.225 Millimeter  
**SEALMASTER TB-24TC Pillow Block Bearings**

Bearing No. TB-24TC

|                           |   |
|---------------------------|---|
| Category                  | Pillow Block Bearings   |
| Inventory                 | 0.0   |
| Manufacturer Name         | REGAL BELOIT  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 2.406   |
| EAN                       | 0662461034101   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 2 Bolt Tap Base Pillow Block  |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 2-18TC  |
| Seals                     | Single Lip Contact  |
| Housing Configuration     | 1 Piece Solid   |
| Inch - Metric             | Inch  |
| Other Features            | Single Row   Standard Duty<br>  Skwezloc   Has Flinger  |
| Long Description          | 2 Bolt Tap Base Pillow Block; 1-1/2" Bore; 1-15/16" Base to Center Height; Concentric Collar Mount; Ball Bearing; Relubricatable; |



## NTN BEARING MFG.CORP

|                               |   |
|-------------------------------|---|
|                               | Cast Iron; Single Lip Contact; Expansion                            |
| Category                      | Pillow Block  |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.40   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer URL              | <a href="http://www.emerson-ept.com">http://www.emerson-ept.com</a> |
| Manufacturer Item Number      | TB-24TC   |
| Manufacturer Internal Number  | 705933  |
| Weight / LBS                  | 6.3   |
| D                             | 1.938 Inch   49.225 Millimeter                                      |
| B                             | 1.938 Inch   49.225 Millimeter                                      |
| Actual Bolt Center to Center  | 3.5 Inch   90Millimeter   |
| d                             | 1.5 Inch   38.1 Millimeter  |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |
| Nominal Bolt Center to Center | 3.5 Inch   90 Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |