



# NTN BEARING MFG.CORP

1.938 Inch | 49.225 Millimeter x 2.343 Inch | 59.5 Millimeter x 2.25 Inch | 57.15 Millimeter SKF SYE 1.15/16 NH Pillow Block Bearings



Bearing No. SYE 1.15/16 NH

SYE 1.15/16 NH Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	4.486
EAN	7316577057518
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Stepped Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	22210
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Double Row   Heavy Duty   Locating Bearing   Open End   With Grub Screw
Long Description	2 Bolt Pillow Block; 1-15/16" Bore; 2-1/4" Base to Center Height; Stepped Sleeve Mount; Spherical



## NTN BEARING MFG.CORP

	Roller Bearing; 6-3/4" Minimum Bolt Spacing; 7-1/4" Bolt Spacing Maximum; Relubric
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	SYE 1.15/16 NH
Weight / LBS	10.5
Bolt Spacing Minimum	6.75 Inch   171.45Millimeter
d	1.938 Inch   49.225 Millimeter
B	2.25 Inch   57.15 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
Nominal Bolt Center to Center	6.6 Inch   167 Millimeter
Bolt Spacing Maximum	7.25 Inch   184.15Millimeter
D	2.343 Inch   59.5 Millimeter
bore diameter:	1.9375 in
bolt center-to-center length:	7 in
overall length:	8.8750 in
base width:	2-1/2 in
overall height:	4.5000 in
expansion type:	Non-Expansion Bearing (Fixed)
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
seal type:	Tri-Guard
bore type:	Round



## NTN BEARING MFG.CORP

radial dynamic load capacity:	21600 lbf
housing construction:	Solid Pillow Block
radial static load capacity:	22400 lbf
base to bore centerline:	2.5000 in
maximum rpm:	2150 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	SYE
locking device:	Concentric Collar
replacement bearing:	22210