



# NTN BEARING MFG.CORP

## TIMKEN E-4BF-TRB-2 7/16 Flange Block Bearings



Bearing No. E-4BF-TRB-2 7/16

E-4BF-TRB-2 7/16 Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	2.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	9.861
EAN	0053893549637
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	4 Bolt Square Flange Block; 2-7/16" Bore; 7.6" Bolt Circle; 5-3/8" Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Tapered Roller Bearing; 4" Length Thru Bore; Rel
Other Features	Double Row   Wide Inner Race   With Set Screw



## NTN BEARING MFG.CORP

Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Manufacturer Item Number	E-4BF-TRB-2 7/16
Weight / LBS	20
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
d	2.438 Inch   61.925 Millimeter
Nominal Bolt Circle Diameter Round	7.6 Inch   193 Millimeter
Bolt Spacing	5.375 Inch   136.525 Millimeter
D	4 Inch   101.6 Millimeter
Shaft Size	2.4375 in
Shaft Size Type	Imperial
Weight	20 lb
UPC Code	053893549637
Dimension B	4 in
Dimension L	6-7/8 in
Dimension A	3-9/16 in
Dimension J	5-3/8 in
Dimension A <sub>2</sub>	3/16 in
Bolt Diameter	5/8 in
Dimension A <sub>1</sub>	1-1/2 in
Dimension D <sup>1</sup>	5-5/16 in
Dimension d <sub>1</sub>	4-1/16 in
e	0.40
X (if F <sub>a</sub> /F <sub>r</sub> ≤ e)	0.87
Y (if F <sub>a</sub> /F <sub>r</sub> > e)	2.17



## NTN BEARING MFG.CORP

X (if $F_a/F_r > e$ )	0.7
Y (if $F_a/F_r > e$ )	2.63
K Factor	1.51
$C_{90}$ Dynamic Load Rating <sup>2</sup>	11600 lb
$C_0$ Static Load Rating	54000 lb
$F_{a-max}$ Maximum Permissible Thrust Load <sup>3</sup>	3454 lb
$F_{r-max}$ Maximum Allowable Slip Fit Radial Load <sup>4</sup>	9500 lb
Max. Speed <sup>5</sup>	2420 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur